



WORTHINGTON
CYLINDERS

Surrounded by Quality™



INDUSTRIAL GAS

ALUMINUM INDUSTRIAL CYLINDERS



SPECIFICATIONS

MODEL	SERVICE PRESSURE	OUTER DIAMETER		FINISHED LENGTH		CYLINDER WEIGHT		WATER VOLUMETRIC CAPACITY		O ₂ CAPACITY	
		INCH	MM	INCH	MM	LBS	KGS	LBS	KGS	CUBIC FT	LITERS
I6	2216	3.20	80.9	11.8	298.5	2.3	1.0	2.2	1.0	5.7	161
I22	2216	5.25	133.4	16.5	419.0	8.4	3.8	8.5	3.9	22.0	623
I33	2216	6.89	175.0	15.3	388.0	14.2	6.4	12.7	5.8	33.0	934
I60	2216	7.25	184.2	23.0	584.0	22.3	10.1	23.1	10.5	60.0	1699
I90	2216	7.25	184.2	32.5	826.0	30.0	13.6	34.7	15.8	90.0	2548
I122	2216	8.00	203.2	36.5	927	40.7	18.5	47.1	21.4	122	3455

Worthington Cylinders' aluminum industrial cylinders

Preferred cylinder package for specialty gas, exotic gas and high-purity gas mixtures

Features

- Lightweight, high strength 6061-T6 alloy
- Corrosion-resistant interior and exterior
- Stringent internal cleaning process ensures compliance with customer specifications
- Available with straight or tapered threads
- Uses Industrial CGA540, 580 or comparable valve, sold separately
- Wide color range available, including a durable, brushed exterior finish

Manufactured to DOT and TC requirements

- U.S. Department of Transportation (DOT) 3AL
- Transport Canada (TC) 3ALM
- Every cylinder inspected and tested by DOT- and TC-authorized independent agency
- Cycle-tested in excess of 100,000 cycles at service pressure
- Minimum burst pressure tested to 2.5 times service pressure without failure



200 Old Wilson Bridge Road
Columbus, Ohio 43085
Toll-free: 866.WC.TANKS (866.928.2657)
Phone: 614.438.3013
Fax: 614.438.3083
Cylinders@WorthingtonIndustries.com
WorthingtonCylinders.com