



WORTHINGTON
CYLINDERS

Surrounded by Quality™



INDUSTRIAL GAS

ALUMINUM CARBON DIOXIDE CYLINDERS



SPECIFICATIONS

PART NO.	SERVICE PRESSURE		CO ₂ MAX. CAP.		N ₂ CAPACITY		OUTSIDE DIAMETER		OVERALL LENGTH		EMPTY WEIGHT		MIN. INTERNAL VOLUME		MIN. WATER WEIGHT		THREAD SIZE
	PSI	BAR	LBS	KG	CU.FT	LITERS	IN.	MM	IN.	MM	LBS	KG.	CU.IN	LITERS	LBS	KG	
2lb	1800	124	2.0	.90	5.8	164	4.38	111.2	8.9	226	2.9	1.32	82	1.3	2.96	1.34	.750-16 UNF-2B
2.5lb	1800	124	2.5	1.13	7.2	204	4.38	111.2	10.4	264	3.3	1.5	102	1.7	3.68	1.67	.750-16 UNF-2B
5lb	1800	124	5.0	2.30	14.5	411	5.25	133.4	14.0	356	6.2	2.8	205	3.4	7.40	3.36	1.125-12 UNF-2B
10lb	1800	124	10.0	4.50	28.9	818	6.89	175.0	16.4	417	12.9	5.9	408	6.7	14.73	6.68	1.125-12 UNF-2B
15lb	1800	124	15.0	6.80	43.3	1226	6.89	175.0	22.8	579	16.8	7.6	612	10.0	22.09	10.02	1.125-12 UNF-2B
20lb	1800	124	20.0	9.07	58.0	1642	8.00	202.2	23	584	22.6	10.3	816	13.4	29.44	13.35	1.125-12 UNF-2B

Worthington Cylinders' CO₂ and mixed-gas cylinders for beverage service

Clean, corrosion-resistant, lightweight cylinders are ideal for dispensing carbonated soft drinks, beers, lagers and other beverages.

Features

- Lightweight, high strength 6061-T6 aluminum alloy improves cylinder system portability while reducing the rigors of material handling.
- Corrosion-resistant interior and exterior
- Brushed exterior provides a durable, low-maintenance finish for years of dependable service.
- Optional carrying handle offers superior valve protection.

Manufactured to DOT and TC requirements

- U.S. Department of Transportation (DOT) 3AL
- Transport Canada (TC) 3ALM
- Every cylinder inspected and tested by DOT- and TC-authorized independent agency
- Cycle-tested in excess of 100,000 cycles at service pressure
- Minimum burst pressure tested to 2.5 times service pressure without failure



200 Old Wilson Bridge Road
Columbus, Ohio 43085
Toll-free: 866.WC.TANKS (866.928.2657)
Phone: 614.438.3013
Fax: 614.438.3083
Cylinders@WorthingtonIndustries.com
WorthingtonCylinders.com