



REFRIGERANT

REFILLABLE



SPECIFICATIONS

MODEL/WATER CAPACITY (LBS.)	30 POUND	123 POUND	1,000 POUND
HEIGHT (IN.)	19.8	54.8	57.3
HEIGHT (MM)	503	1,392	1,455
WATER CAPACITY (KG)	13.6	55.6	450
NOMINAL TARE WEIGHT (LBS.)	21	58	334
NOMINAL TARE WEIGHT (KG)	9.3	26.3	151.5
CYLINDER DIAMETER (IN.)	9.1	10	30
CYLINDER DIAMETER (MM)	231.1	254	762
CYLINDER VOLUME (CU. IN.)	830	3,393	27,461
CYLINDER VOLUME (LITERS)	13.6	55.6	450
COLLAR DIAMETER (IN.)	8	3.9	16
COLLAR DIAMETER (MM)	203.2	98.4	406.4
COLLAR HEIGHT (IN.)	5.1	N/A	6.9
COLLAR HEIGHT (MM)	130	N/A	175
FOOTRING DIAMETER (IN.)	6.9	10	22
FOOTRING DIAMETER (MM)	175	254	558.8
STANDARD SPECIFICATION	DOT-4BA-400	DOT-4BW-400	DOT-4BW-260
SERVICE PRESSURE (PSIG)	400	400	260
SERVICE PRESSURE (BAR)	27.6	27.6	17.9
TEST PRESSURE (PSIG)	800	800	520
TEST PRESSURE (BAR)	55.2	55.2	35.9
OPTIONAL SPECIFICATION	N/A	N/A	DOT-4BW-400
SERVICE PRESSURE (PSIG)	N/A	N/A	400
SERVICE PRESSURE (BAR)	N/A	N/A	27.6
TEST PRESSURE (PSIG)	N/A	N/A	800
TEST PRESSURE (BAR)	N/A	N/A	55.2

All tare weights and dimensions are approximate.
For more information on 400 psig 1,000 lb. DOT-4BW tare weight, call Worthington Cylinders.
Cylinder photos are not shown to scale.