



**SPECIFICATIONS**

MODEL/SIZE (LBS.)	2	6	25.5	60	100	200	420
HEIGHT (IN.)	16.9	22.1	32.9	44.1	48	40	52
HEIGHT (MM)	429	561	836	1,120	1,219	1,016	1,321
WATER CAPACITY (LBS.)	4.5	15	61	142.9	239	474	1,000
WATER CAPACITY (KG)	2	6.8	27.7	64.8	108.4	215	454
NOMINAL TARE WEIGHT (LBS.)	5.5	8	25.9	48.1	74.8	158	298
NOMINAL TARE WEIGHT (KG)	2.5	3.6	11.7	21.8	33.9	71.6	135
CYLINDER DIAMETER (IN.)	4	6.3	9.1	12	14.7	24	30
CYLINDER DIAMETER (MM)	102	160	231	305	373	610	762
CYLINDER VOLUME (CU. IN.)	125	415	1,688	3,955	6,616	13,120	27,731
CYLINDER VOLUME (LITER)	2	6.8	27.7	64.8	108.4	215	454
COLLAR DIAMETER (IN.)	3	5.7	6.5	6.5	6.5	16	16
COLLAR DIAMETER (MM)	76	144.8	165	165	165	406	406
COLLAR HEIGHT (IN.)	4.3	6.5	5.1	5.1	5.1	6.9	6.9
COLLAR HEIGHT (MM)	109	165	130	130	130	175	175
FOOTRING DIAMETER (IN.)	3.9	6.3	7.8	12	14.5	19	22
FOOTRING DIAMETER (MM)	99	160	198	305	368	483	559
STANDARD SPECIFICATION	DOT-4BA-260	DOT-4E-260	DOT-4BW-260	DOT-4BW-260	DOT-4BW-260	DOT-4BW-260	DOT-4BW-260

All dimensions are approximate.